

EVOKO NASO

TECHNICAL SPECIFICATION

TECHNICAL INFO

Display

- 8" LCD 4:3 1024x768
- Capacitive multi-touch

Connectivity

• Ethernet

1000base-t/ 100base-tx/
10base-te

• Wifi

802.11b/g/n/ac 2.4ghz

• RFID

NFCIP-1, NFCIP-2 protocol
ISO/IEC 14443A, ISO/IEC
14443B PICC mode via host
interface

MIFARE PCD encryption
mechanism (MIFARE 1K/4K)

NFC Forum tag 1 to 4,
(MIFARE Ultralight, Jewel,
Open FeliCa tag
MIFARE DESFire)

• Bluetooth

Bluetooth 4.2 (BLE)

Power

• Power over Ethernet

PoE RJ45
802.3at PD type 1 (13W)

• DC-Power

5VDC (DC-Power supply sold
separately)

Other

• Sensors

Proximity sensor
Ambient light sensor

• Mounting

Mounting options for both
standard and glass walls
5-way cable exit option for
easy and neat installation

* = In road map

USER INTERFACE LANGUAGES

- Arabic
- Catalan
- Chinese, Simplified
- Chinese, Traditional
- Czech
- Danish
- Dutch
- English
- Estonian
- Finnish
- French
- Galician
- German
- Italian
- Japanese
- Latvian
- Lithuanian
- Norwegian
- Polish
- Portuguese
- Russian
- Spanish
- Swedish

ARTICLE NUMBERS

Evoko Naso: ENX1001
Room hosting: ENX1031
Rose license: ENX1032
Pepper license: ENX1033
Guava license: ENX1034
Interactive maps: ENX1035

MEASUREMENT AND WEIGHT

Product

- 195 x 195 x 35mm
[7.7 x 7.7 x 1.37in]
0,9 kg [2 lbs]

Retail Sales kit package

- 290 x 290 x 73mm
[11.4 x 11.4 x 2.9in]
1,6 kg [3.6 lbs]

COMPATIBLE PLATFORMS

- Microsoft Office 365

MORE FEATURES

Remote management with
multi-site support.

Real-time monitoring &
statistics.

3-way indirect light aura to
make room status visible
already from a distance.

VC automation.

Sensor integration.

Open API for third party
integration.*

