

<b>Display diagonal</b>	33.2 Inches (843.09 mm)
<b>Active Display Area</b>	596.16 x 596.16 mm
<b>Resolution</b>	1.920 x 1.920 (QHD) @ 60 Hz / 1:1
<b>Panel Type</b>	IPS Hard-Coating (3H), Anti-Glare Treatment
<b>Brightness</b>	450 cd/m2
<b>Contrast</b>	1.000:1
<b>Viewing Angle</b>	178° H/V
<b>Colors</b>	8 Bit + FRC, 16.7M colors
<b>Color Gamut</b>	NTSC 72%
<b>Anti-Glare (Haze)</b>	25%
<b>Orientation</b>	Landscape / Portrait
<b>Connections</b>	1x USB, 1x RJ out, 1x RJ45c, 1x RS232c, 1x Micro SD Card, 1x USB Type C (Power Supply)
<b>Operation Time</b>	24 / 7
<b>Operating Conditions</b>	Temperature 0°C to 50°C / Humidity 10-80%
<b>Storage Conditions</b>	Temperature -20°C to 50°C / Humidity 5-90%
<b>Delivered Contents</b>	Power Adapter, Mounting Plate
<b>Integrated Computer</b>	BrightSign 4K Player integrated (1920x1920px) VIDEO H.265/H.264 .MOV, .MP4, .MKV, .TS IMAGE BMP, JPEG, PNG  WI-FI/Bluetooth Module (Optional)
<b>BrightSign Supported</b>	BrightAuthor®, BrightBeacon, BrightWall, Zones, Mosaic Mode, IP Streaming, Live Feeds, Tagging, BrightSign App (iOS), Geo-Fencing (requires USB dongle), Sign Preview, Remote Snapshot, Networking, B-eploy
<b>Dimensions</b>	615.2 x 615.2 x 35 mm (Even Thickness) / Bezel 6.6 mm (Even Bezel)
<b>VESA</b>	300 x 300 mm
<b>Weight</b>	7.8 Kg (Net)
<b>Power Consumption</b>	Operation 82W / Standby 0.5W (24V/6A, Source 100-240V 60W)
<b>Certifications</b>	CE
<b>Warranty</b>	2 Years Parts & Labor